



US009638299B2

(12) **United States Patent**
Nass et al.

(10) **Patent No.:** **US 9,638,299 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **ACTUATING DEVICE**

(71) Applicant: **Kiekert Aktiengesellschaft**,
Heiligenhaus (DE)

(72) Inventors: **Ulrich Nass**, Muelheim/Ruhr (DE);
Christian Barmseidtt, Duisburg
(DE); **Carsten Fuchs**, Benrath (DE);
Ludger Graute, Essen (DE)

(73) Assignee: **Kiekert Aktiengesellschaft**,
Heiligenhaus (DE)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 107 days.

(21) Appl. No.: **14/219,621**

(22) Filed: **Mar. 19, 2014**

(65) **Prior Publication Data**

US 2014/0203570 A1 Jul. 24, 2014

Related U.S. Application Data

(63) Continuation of application No. 14/119,590, filed as
application No. PCT/DE2012/000561 on May 26,
2012.

(30) **Foreign Application Priority Data**

May 28, 2011 (DE) 20 2011 101 230 U

(51) **Int. Cl.**
E05C 3/06 (2006.01)
F16H 21/44 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **F16H 21/44** (2013.01); **E05B 53/005**
(2013.01); **E05B 79/20** (2013.01); **E05B 81/20**
(2013.01);
(Continued)

(58) **Field of Classification Search**

CPC E05B 79/20; E05B 81/14; E05B 81/25;
E05B 53/005; Y10T 292/0931
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,374,597 A * 2/1983 Mochida F16C 1/10
292/336.3
5,531,489 A * 7/1996 Cetnar E05B 85/12
292/225

(Continued)

FOREIGN PATENT DOCUMENTS

DE 43 27 782 A1 3/1994
DE 10 2004 052 599 A1 5/2006

(Continued)

OTHER PUBLICATIONS

International Search Report for corresponding patent application
No. PCT/DE2012/000561 dated Nov. 7, 2012.

Primary Examiner — Mark Williams

(74) *Attorney, Agent, or Firm* — Renner, Otto, Boisselle
& Sklar, LLP

(57) **ABSTRACT**

The invention relates to an actuating device for joint action
upon at least two different elements of a motor vehicle door
lock, with at least one sheathed cable having a core and
sheath, wherein the sheathed cable is provided in the longi-
tudinal extent thereof with at least two force transmission
units which are designed for interaction with a first element
at one end and with a second element at the other end upon
action on the sheathed cable, and one of the two elements is
designed as an actuating lever, wherein the other element is
a closing/opening element operating on a locking mecha-
nism.

14 Claims, 2 Drawing Sheets

